

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Hexamethylene diacrylate
Registration number (REACH)	this information is not available
CAS number	13048-33-4
Alternative name(s)	6-(prop-2-enoyloxy)hexyl prop-2-enoate
Article number	A0053769

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	General use
--------------------------	-------------

1.3 Details of the supplier of the safety data sheet

Chemos GmbH & Co. KG
Sonnenring 7
84032 Altdorf
Germany

Telephone: +49 871-966346-0
Telefax: +49 871-966346-13
e-mail: chemos@chemos.de
Website: <http://www.chemos.de/>

e-mail (competent person) chemos@chemos.de

1.4 Emergency telephone number

Emergency information service	+49 89 1 92 40
-------------------------------	----------------

Poison centre				
Country	Name	Postal code/ city	Telephone	Telefax
United Kingdom	National Poison Information Centre Medical Toxicology Unit	SE14 5ER London	+44 171 635 91 91	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4S	skin sensitisation	1	Skin Sens. 1	H317
4.1A	hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word warning

- Pictograms

GHS07, GHS09



- Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
P501 Dispose of contents/container to industrial combustion plant.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Hexamethylene diacrylate
Identifiers	
CAS No	13048-33-4
EC No	235-921-9
Molecular formula	C ₁₂ H ₁₈ O ₄
Molar mass	226.3 g/mol

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	24.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	2.77 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.007 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.001 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	2.7 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0.493 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.049 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0.094 mg/kg	terrestrial organisms	soil	short-term (single instance)

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Colour	various
Odour	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	7.8 °C
Initial boiling point and boiling range	98.82 °C at 0.71 mbar
Flash point	>110 °C at 1,013 hPa
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapour pressure	0.001 hPa at 20 °C
Density	1.022 g/cm ³ at 20 °C

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

Vapour density	this information is not available
----------------	-----------------------------------

Solubility(ies)

- Water solubility	343 mg/l at 20 °C
--------------------	-------------------

Partition coefficient

- n-octanol/water (log KOW)	2.81 (25 °C) (ECHA)
- Soil organic carbon/water (log KOC)	2.1 (ECHA)

Auto-ignition temperature	235 °C at 1,013 hPa (ECHA) (auto-ignition temperature (liquids and gases))
---------------------------	--

Viscosity

- Kinematic viscosity	6.75 mm ² /s at 20 °C
- Dynamic viscosity	6.9 mPa s at 20 °C

Explosive properties	none
Oxidising properties	none

9.2 Other information

Solvent content	100 %
Temperature class (EU, acc. to ATEX)	T3 (maximum permissible surface temperature on the equipment: 200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

If heated:

Exothermic polymerisation

If exposed to light:

Exothermic polymerisation.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

UV-radiation/sunlight.

10.5 Incompatible materials

Oxidisers, Reducing agents

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
LC50	0.38 mg/l	fish	96 h
EC50	8.3 mg/l	aquatic invertebrates	24 h
ErC50	2.33 mg/l	algae	72 h

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

Aquatic toxicity (chronic)			
Endpoint	Value	Species	Exposure time
LC50	0.47 mg/l	aquatic invertebrates	21 d
EC50	0.15 mg/l	aquatic invertebrates	21 d

Biodegradation

The substance is readily biodegradable. The relevant substances of the mixture are readily biodegradable.

12.2 Persistence and degradability

Process of degradability		
Process	Degradation rate	Time
carbon dioxide generation	60 – 70 %	28 d

12.3 Bioaccumulative potential

Data are not available.

n-octanol/water (log KOW)	2.81 (25 °C) (ECHA)
---------------------------	---------------------

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	2.1 (ECHA)
--	------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packageings

It is a dangerous waste; only packageings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

SECTION 14: Transport information

14.1 UN number	3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical name	Hexamethylene diacrylate
14.3 Transport hazard class(es)	
Class	9 (environmentally hazardous)
14.4 Packing group	III (substance presenting low danger)
14.5 Environmental hazards	hazardous to the aquatic environment
14.6 Special precautions for user	
Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class	9
Classification code	M6
Packing group	III
Danger label(s)	9, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	274, 335, 375, 601
Exempted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	-
Hazard identification No	90
Emergency Action Code	3Z



International Maritime Dangerous Goods Code (IMDG)

UN number	3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class	9
Marine pollutant	yes (hazardous to the aquatic environment)

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

Packing group	III
Danger label(s)	9, fish and tree
	
Special provisions (SP)	274, 335, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A
International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	3082
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
Class	9
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	III
Danger label(s)	9, fish and tree
	
Special provisions (SP)	A97, A158, A197
Excepted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Deco-Paint Directive (2004/42/EC)

VOC content	100 %
-------------	-------

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content	0 %
-------------	-----

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Hexamethylene diacrylate

Version number: GHS 1.0

Date of compilation: 2019-12-02

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.